


V-Belts

PU80A transparent smooth



approx. 84° Shore A (±3)

Recommended Pretension 4...8%

Coeff. of friction μ steel approx. 0,65

Coeff. of friction μ PE approx. 0,35

Coeff. of friction μ HDPE approx. 0,3

FDA/EC compliant

Article no.	Dimensions mm	approx. weight kg/100m	Standard roll		Recommended min. pulley \varnothing		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			m	ft	mm	inch	Standard N	Standard kg	Standard lbs
FBKP80A06TR	6x4 (Y)	2,3	100	328	40	1,6	31	6,1	13,5
FBKP80A08TR	8x5 (M)	4	100	328	45	1,8	53	10,5	23,2
FBKP80A10TR	10x6 (Z)	6	50	164	55	2,2	80	16,0	35,4
FBKP80A13TR	13x8 (A)	10	50	164	85	3,3	138	27,5	60,7
FBKP80A17TR	17x11 (B)	18	50	164	110	4,3	245	49,0	108,0
FBKP80A22TR	22x14 (C)	29	50	164	150	5,9	409	81,7	180,1
FBKP80A32TR	32x20 (D)	62	25	82	220	8,7	856	171,1	377,1

Characteristics



FDA (Food and Drug Administration)

FDA/EC conformity for direct food contact



Vegan

Use of raw materials from non-animal origin

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 04/2026