


V-Belts

# PU80A capri blue smooth



approx. 84° Shore A (±3)

Recommended Pretension 3...6%

Coeff. of friction  $\mu$  steel approx. 0,65

Coeff. of friction  $\mu$  PE approx. 0,35

Coeff. of friction  $\mu$  HDPE approx. 0,3

FDA/EC compliant

Article no.	Dimensions mm	approx. weight kg/100m	Standard roll		Recommended min. pulley $\varnothing$		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			m	ft	mm	inch	Standard N	Standard kg	Standard lbs
FBKJ6YLGM	6x4 (Y)	2,3	100	328	40	1,6	25	5,0	11,0
FBKJ8MLGM	8x5 (M)	4	100	328	45	1,8	43	8,5	18,8
FBKJ10ZLGM	10x6 (Z)	6	50	164	55	2,2	65	13,0	28,6
FBKJ13ALGM	13x8 (A)	10	50	164	85	3,3	111	22,3	49,1
FBKJ17BLGM	17x11 (B)	18	50	164	110	4,3	198	39,7	87,4
FBKJ22CLGM	22x14 (C)	29	50	164	150	6	331	66,2	145,8

Characteristics



**FDA (Food and Drug Administration)**  
FDA/EC conformity for direct food contact



**Vegan**  
Use of raw materials from non-animal origin



**Metal detectable**



**X-ray detectable**

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 05/2026