



**Quality:** PU85A  
**Article No.:** FBKP85A32  
**Color:** green

**GENERAL PROFILE INFORMATION**

Profile Category	V-belts	k1% relaxed (standard)	127,3 N   726,3 lbf
Profile design	Without reinforcement	k1% static (standard)	159,1 N   907,9 lbf
Type of reinforcement	n/a	Weight	62 kg/100m
Processing Type	n/a	Temperature Range	-20°...+60°C
Recommended Min. pulley Ø	250 mm	Standard Roll	25 m
Recommended Pretension	4...8%	Chemical Resistance	upon request

<b>SPECIFICATIONS</b>	<b>PROFILE</b>	<b>COATING</b>
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	88° Shore A ( $\pm 3$ )	n/a
Color	green	n/a
Dimensions	32x20 mm (D)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,6   PE: 0,35   HDPE: 0,3	n/a
Features	n/a	n/a
n/a	n/a	n/a

**CONFORMITY**

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 01/2026