

V-Belts

PU85A green smooth, Reinforced Aramid



Article no.	Dimensions mm	approx. weight kg/100m	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt		TRANSPORT max. conveying weight				
			m	ft	mm	inch	Standard N	Overlap N	Standard		Overlap		
										kg	lbs	kg	lbs
FBZKP85A08A	8x5 (M)	4	100	328	60	2,4	63	177	12,5	27,6	35,5	78,2	
FBZKP85A10A	10x6 (Z)	6	50	164	70	2,8	96	184	19,1	42,1	36,7	80,9	
FBZKP85A13A	13x8 (A)	10	50	164	100	3,9	164	305,0	32,8	72,3	61	134,5	
FBZKP85A17A	17x11 (B)	18	50	164	140	5,5	292	329	58,3	128,6	65,8	145,1	
FBZKP85A22A	22x14 (C)	29	50	164	180	7,1	486	651	97,3	214,4	130,2	287	
FBKK32DGGA	32x20 (D)	62	40	131	275	10,8	1019		203,7	449,0			

approx. 88° Shore A (±3)

Max. Preload

Standard	1,5 %
Overlap	1,5 %

Coeff. of friction μ steel approx. 0,6

Coeff. of friction μ PE approx. 0,35

Coeff. of friction μ HDPE approx. 0,3

Characteristics



with reinforcement
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 06/2026