



Quality: PU85A
Article No.: FBZKP85A17A
Color: green



GENERAL PROFILE INFORMATION			
Profile Category	V-belts	k1% relaxed (standard)	194,5 N 1109,4 lbf
Profile design	with reinforcement	k1% static (standard)	243,1 N 1386,8 lbf
Type of reinforcement	Aramid	k1% relaxed (overlap)	219,5 N 1252 lbf
Processing Type	n/a	k1% static (overlap)	274,3 N 1565 lbf
Recommended Min. pulley Ø	140 mm	Standard Roll	50 m
Max. Preload	1,5% (Stoß) n/a (Überlapp)	Chemical Resistance	upon request
Weight	18 kg/100m		
Temperature Range	-20°...+60°C		

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	88° Shore A (±3)	n/a
Color	green	n/a
Dimensions	17x11 mm (B)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,6 PE: 0,35 HDPE: 0,3	n/a
Features	with reinforcement	n/a
n/a	n/a	n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 04/2026