



Quality: PU85A
Article No.: FBZKP85A17PS
Color: sapphire blue



GENERAL PROFILE INFORMATION

| | | | |
|---------------------------|----------------------------|------------------------|---------------------|
| Profile Category | V-belts | k1% relaxed (standard) | 134,2 N 765,5 lbf |
| Profile design | with reinforcement | k1% static (standard) | 167,7 N 956,9 lbf |
| Type of reinforcement | Polyester | k1% relaxed (overlap) | 93,1 N 531,3 lbf |
| Processing Type | n/a | k1% static (overlap) | 116,4 N 664,1 lbf |
| Recommended Min. pulley Ø | 120 mm | Standard Roll | 50 m |
| Max. Preload | 2% (Stoß) n/a (Überlapp) | Chemical Resistance | upon request |
| Weight | 18 kg/100m | | |
| Temperature Range | -30°...+60°C | | |

SPECIFICATIONS

PROFILE

COATING

| | | |
|-----------------------------------|------------------------------------|-----|
| Type of material | Polyurethane | n/a |
| Approx. Material Hardness (Shore) | 88° Shore A (±3) | n/a |
| Color | sapphire blue | n/a |
| Dimensions | 17x11 mm (B) | n/a |
| Surface | smooth | n/a |
| approx. Coefficient of Friction | Steel: 0,6 PE: 0,35 HDPE: 0,3 | n/a |
| Features | Hydrolysis resistance | n/a |
| n/a | microbial resistant | n/a |
| n/a | Cold-flexible | n/a |
| n/a | with reinforcement | n/a |
| n/a | FDA (Food and Drug Administration) | n/a |
| n/a | n/a | n/a |

CONFORMITY

- REACH EC 1907/2006 in the current versions
- EC 1935/2004 in the current versions
- EC 10/2011 in the current versions
- FDA (Food and Drug Administration)

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 06/2026