

## V-Belts

# PU85A ultramarine blue smooth, Reinforced Glass fibre PU, weldable



Article no.	Dimensions	Cross section	approx. weight	Standard roll		Recommended min. pulley ØØ		Fmax/belt (standard)		Fmax/belt (overlap)	
	mm	cm <sup>2</sup>	kg/100m	m	ft	mm	inch	kg	lbs	kg	lbs
FBZKP85A17	17x11 (B)	1,46	18	50	164	180	7,1	55,4	122	n/a	n/a
FBZKP85A22	22x14 (C)	2,4	29	50	164	220	8,7	92,4	203,3	n/a	n/a

approx. 88° Shore A

Recommended Pretension	0.5...2%
------------------------	----------

Coeff. of friction $\mu$ steel approx.	0,6
--	-----

Coeff. of friction $\mu$ PE approx.	0,35
-------------------------------------	------

Coeff. of friction $\mu$ HDPE approx.	0,3
---------------------------------------	-----

## Characteristics



### with reinforcement

for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 09/2025