



GENERAL PROFILE INFORMATION



Quality: PU85A plus Article No.: FBKP85A08BP Color: blue

Profile Category	V-belts	Fmax/belt (standard)	13,2 kg
Profile design	Without reinforcement	Fmax/Belt (overlap)	n/a
Type of reinforcement	n/a	Weight	4 kg/100m
Processing Type	n/a	Temperature Range	-20°+60°C
Recommended Min. pulley Ø	50 mm	Standard Roll	100 m
Recommended Pretension	36%	Chemical Resistance	upon request

LOW

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	88° Shore A	n/a
Color	blue	n/a
Dimensions	8x5 mm (M)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,6 PE: 0,35 HDPE: 0,3	n/a
Features	Low elongation	n/a
n/a	n/a	n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 07/2025