

V-Belts

**PU90A white smooth**



approx. 92° Shore A (±3)

Recommended Pretension 3...5%

Coeff. of friction  $\mu$  steel approx. 0,5

Coeff. of friction  $\mu$  PE approx. 0,3

Coeff. of friction  $\mu$  HDPE approx. 0,25

Article no.	Dimensions mm	approx. weight kg/100m	Standard roll		Recommended min. pulley $\varnothing$		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			m	ft	mm	inch	Standard N	Standard kg	lbs
FBKP90A08	8x5 (M)	4	100	328	60	2,4	72	14,4	31,8
FBKP90A10	10x6 (Z)	6	50	164	80	3,2	110	22,0	48,4
FBKP90A13	13x8 (A)	10	50	164	105	4,2	189	37,7	83,1
FBKP90A17	17x11 (B)	18	50	164	140	5,5	335	67,1	147,9
FBKP90A22	22x14 (C)	29	50	164	200	7,9	559	111,9	246,6

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 05/2026