





Quality: PU90A
Article No.: FBKP90A08

Color: white

GENERAL PROFILE INFORMATION				
Profile Category	V-belts	k1% relaxed (standard)	n/a 14,4 lbf/inch	
Profile design	Without reinforcement	k1% static (standard)	82,3 N/mm 18,0 lbf/inch	
Type of reinforcement	n/a	Weight	4 kg/100m	
Processing Type	n/a	Temperature Range	-20°+60°C	
Recommended Min. pulley \emptyset	60 mm	Standard Roll	100 m	
Recommended Pretension	35%	Chemical Resistance	upon request	

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	92° Shore A	n/a
Color	white	n/a
Dimensions	8x5 mm (M)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,5 PE: 0,3 HDPE: 0,25	n/a
Features	n/a	n/a
n/a	n/a	n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 11/2025