

V-Belts

PU90A white smooth, Reinforced Polyester



Article no.	Dimensions mm	approx. weight kg/100m	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt		TRANSPORT max. conveying weight				
			m	ft	mm	inch	Standard N	Overlap N	Standard		Overlap		
										kg	lbs	kg	lbs
FBZKP90A08P	8x5 (M)	4	100	328	65	2,6	72	176	14,4	31,8	35,2	77,5	
FBZKP90A10P	10x6 (Z)	6	50	164	85	3,3	110	245	22,0	48,4	48,9	107,8	
FBZKP90A13P	13x8 (A)	10	50	164	110	4,3	189	292	37,7	83,1	58,4	128,6	
FBZKP90A17P	17x11 (B)	18	50	164	150	5,9	335	737	67,1	147,9	147,4	324,9	
FBZKP90A22P	22x14 (C)	29	50	164	210	8,3	559	1120	111,9	246,6	224,0	493,8	

approx. 92° Shore A (±3)

Max. Preload

Standard	2 %
Overlap	3 %

Coeff. of friction μ steel approx. 0,5

Coeff. of friction μ PE approx. 0,3

Coeff. of friction μ HDPE approx. 0,25

Characteristics



with reinforcement
for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 06/2026