





Quality: PU90A Article No.: FBZKP90A17P Color: white



GENERAL PROFILE INFORMATION **Profile Category** V-belts Fmax/belt (standard) 69,1 kg Fmax/Belt (overlap) Profile design with reinforcement 120 kg Type of reinforcement Weight 18 kg/100m Polyester -20°...+60°C Processing Type Temperature Range n/a Recommended Min. pulley Ø 150 mm Standard Roll 50 m **Recommended Pretension** 0.5...2% **Chemical Resistance** upon request

| PROFILE                           | COATING  |
|-----------------------------------|--|
| Polyurethane                      | n/a  |
| 92° Shore A                       | n/a  |
| white                             | n/a  |
| 17x11 mm (B)                      | n/a  |
| smooth                            | n/a  |
| Steel: 0,5   PE: 0,3   HDPE: 0,25 | n/a  |
| with reinforcement                | n/a  |
| n/a                               | n/a  |
|                                   | Polyurethane<br>92° Shore A<br>white<br>17x11 mm (B)<br>smooth<br>Steel: 0,5   PE: 0,3   HDPE: 0,25<br>with reinforcement<br>n/a<br>n/a<br>n/a |

## CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 07/2025