

V-Belts

PU95A beige smooth, Reinforced Polyester



Article no.	Dimensions mm	approx. weight kg/100m	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt		TRANSPORT max. conveying weight			
			m	ft	mm	inch	Standard N	Overlap N	Standard		Overlap	
									kg	lbs	kg	lbs
FBKM13ABGA	13x8 (A)	10	50	164	130	5	205	302	41,0	90,3	60,3	133,0
FBKM17BBGA	17x11 (B)	18	50	164	175	6,8	365	755	72,9	160,7	150,9	332,7
FBKM22CBGA	22x14 (C)	29	50	164	250	9,7	608	1149	121,6	268,0	229,9	506,6

approx. 95° Shore A (±3)

Max. Preload

Standard 2 %

Overlap 3 %

Coeff. of friction μ steel approx. 0,45

Coeff. of friction μ PE approx. 0,25

Coeff. of friction μ HDPE approx. 0,2

FDA/EC compliant

Characteristics



FDA (Food and Drug Administration)

FDA/EC conformity for direct food contact



with reinforcement

for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 05/2026