

V-Belts

PU95A beige smooth, Reinforced Polyester

Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt		TRANSPORT max. conveying weight					
			mm	kg/100m	m	ft	mm	inch	Standard N	Overlap N	Standard kg	Overlap lbs	Standard kg	Overlap lbs
FBKM13ABGA	13x8 (A)	10	50	164	130	5	205	302	41,0	90,3	60,3	133,0		
FBKM17BBGA	17x11 (B)	18	50	164	175	6,8	365	755	72,9	160,7	150,9	332,7		
FBKM22CBGA	22x14 (C)	29	50	164	250	9,7	608	1149	121,6	268,0	229,9	506,6		

approx. 95° Shore A (± 3)

Max. Preload

Standard 2 %

Overlap 3 %

Coeff. of friction μ steel 0,45 approx.Coeff. of friction μ PE 0,25 approx.Coeff. of friction μ HDPE 0,2 approx.

FDA/EC compliant

Characteristics


FDA (Food and Drug Administration)
 FDA/EC conformity for direct food contact

with reinforcement
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 01/2026