





Quality: PU95A

Article No.: FBKM13ABGA

Color: beige



FDA .	

GENERAL PROFILE INFORMATION				
Profile Category	V-belts	k1% relaxed (standard)	102,5 N 584,5 lbf	
Profile design	with reinforcement	k1% static (standard)	128,1 N 730,6 lbf	
Type of reinforcement	Polyester	k1% relaxed (overlap)	100,6 N 573,7 lbf	
Processing Type	n/a	k1% static (overlap)	125,7 N 717,1 lbf	
Recommended Min. pulley Ø	130 mm	Standard Roll	50 m	
Recommended Pretension	n/a	Chemical Resistance	upon request	
Weight	10 kg/100m			
Temperature Range	-20°+60°C			

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	95° Shore A (±3)	n/a
Color	beige	n/a
Dimensions	13x8 mm (A)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,45 PE: 0,25 HDPE: 0,2	n/a
Features	FDA (Food and Drug Administration)	n/a
n/a	with reinforcement	n/a
n/a	n/a	n/a

CONFORMITY

FDA (Food and Drug Administration)

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 12/2025