



Quality: PU95A
Article No.: FBKM13ABGA
Color: beige



GENERAL PROFILE INFORMATION			
Profile Category	V-belts	Fmax/belt (standard)	40 kg
Profile design	with reinforcement	Fmax/Belt (overlap)	67,5 kg
Type of reinforcement	Polyester	Weight	10 kg/100m
Processing Type	n/a	Temperature Range	-20°...+60°C
Recommended Min. pulley Ø	130 mm	Standard Roll	50 m
Recommended Pretension	0.5...2%	Chemical Resistance	upon request

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	95° Shore A	n/a
Color	beige	n/a
Dimensions	13x8 mm (A)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,45 PE: 0,25 HDPE: 0,2	n/a
Features	FDA (Food and Drug Administration)	n/a
n/a	with reinforcement	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a

CONFORMITY

FDA (Food and Drug Administration)

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 07/2025