



Quality: PU95A
Article No.: FBKM17BBGA
Color: beige



GENERAL PROFILE INFORMATION

| | | | |
|---------------------------|--------------------|------------------------|----------------------|
| Profile Category | V-belts | k1% relaxed (standard) | 182,3 N 1040,1 lbf |
| Profile design | with reinforcement | k1% static (standard) | 227,9 N 1300,1 lbf |
| Type of reinforcement | Polyester | k1% relaxed (overlap) | 251,6 N 1435,2 lbf |
| Processing Type | n/a | k1% static (overlap) | 314,5 N 1793,9 lbf |
| Recommended Min. pulley Ø | 175 mm | Standard Roll | 50 m |
| Recommended Pretension | n/a | Chemical Resistance | upon request |
| Weight | 18 kg/100m | | |
| Temperature Range | -20°...+60°C | | |

| SPECIFICATIONS | PROFILE | COATING |
|-----------------------------------|------------------------------------|---------|
| Type of material | Polyurethane | n/a |
| Approx. Material Hardness (Shore) | 95° Shore A (±3) | n/a |
| Color | beige | n/a |
| Dimensions | 17x11 mm (B) | n/a |
| Surface | smooth | n/a |
| approx. Coefficient of Friction | Steel: 0,45 PE: 0,25 HDPE: 0,2 | n/a |
| Features | FDA (Food and Drug Administration) | n/a |
| n/a | with reinforcement | n/a |
| n/a | n/a | n/a |
| n/a | n/a | n/a |
| n/a | n/a | n/a |
| n/a | n/a | n/a |

CONFORMITY

FDA (Food and Drug Administration)

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 12/2025