





Quality: PU95A Article No.: FBKM22CBGA

Color: beige



GENERAL PROFILE INFORMATION			
Profile Category	V-belts	k1% relaxed (standard)	304,0 N 1734,5 lbf
Profile design	with reinforcement	k1% static (standard)	380,0 N 2168,1 lbf
Type of reinforcement	Polyester	k1% relaxed (overlap)	383,1 N 2185,6 lbf
Processing Type	n/a	k1% static (overlap)	478,9 N 2732,1 lbf
Recommended Min. pulley Ø	250 mm	Standard Roll	50 m
Recommended Pretension	n/a	Chemical Resistance	upon request
Weight	29 kg/100m		
Temperature Range	-20°+60°C		

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	95° Shore A (±3)	n/a
Color	beige	n/a
Dimensions	22x14 mm (C)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,45 PE: 0,25 HDPE: 0,2	n/a
Features	FDA (Food and Drug Administration)	n/a
n/a	with reinforcement	n/a
n/a	n/a	n/a

CONFORMITY

FDA (Food and Drug Administration)

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 12/2025