

V-Belts

**PU95A beige smooth, Reinforced Polyester**



Article no.	Dimensions	Cross section	approx. weight	Standard roll		Recommended min. pulley Ø		Fmax/belt (s- tandard)		Fmax/belt (overlap)	
	mm	cm <sup>2</sup>	kg/100m	m	ft	mm	inch	kg	lbs	kg	lbs
FBZKP95A13PV	13x8 (A)	0,82	10	50	164	100	3,9	34	74,8	n/a	n/a
FBZKP95A17PV	17x11 (B)	1,46	18	50	164	130	5	61,2	134,6	n/a	n/a
FBZKP95A22PV	22x14 (C)	2,4	29	50	164	190	7,4	102	224,4	n/a	n/a

approx. 95° Shore A

Recommended Pretension 0.5...2%

Coeff. of friction  $\mu$  steel approx. 0,45

Coeff. of friction  $\mu$  PE approx. 0,25

Coeff. of friction  $\mu$  HDPE approx. 0,2

FDA/EC compliant

**Characteristics**



**FDA (Food and Drug Administration)**  
 FDA/EC conformity for direct food contact



**with reinforcement**  
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 11/2024