

V-Belts

TPE40D beige smooth



approx. 40D / 95A

Recommended Pretension 2...4%

Coeff. of friction μ steel approx. 0,5

Coeff. of friction μ PE approx. 0,25

Coeff. of friction μ HDPE approx. 0,2

FDA/EC compliant

| Article no. | Dimensions mm | approx. weight kg/100m | Standard roll | | Recommended min. pulley \varnothing | | DRIVE Fmax/belt | TRANSPORT max. conveying weight | |
|-------------|------------------|---------------------------|---------------|-----|---------------------------------------|------|--------------------|------------------------------------|-----------------|
| | | | m | ft | mm | inch | Standard N | Standard kg | Standard lbs |
| FBKR08MBG | 8x5 (M) | 4 | 100 | 328 | 60 | 2,4 | 73 | 14,5 | 32,1 |
| FBKR10ZBG | 10x6 (Z) | 6 | 50 | 164 | 80 | 3,2 | 111 | 22,2 | 48,8 |
| FBKR13ABG | 13x8 (A) | 10 | 50 | 164 | 105 | 4,2 | 190 | 38,0 | 83,8 |
| FBKR17BBG | 17x11 (B) | 18 | 50 | 164 | 140 | 5,5 | 338 | 67,7 | 149,2 |
| FBKR22CBG | 22x14 (C) | 29 | 50 | 164 | 200 | 7,9 | 564 | 112,9 | 248,7 |

Characteristics



FDA (Food and Drug Administration)

FDA/EC conformity for direct food contact



Cold-flexible

Particularly flexible at low temperatures down to -30°C

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 05/2026