


V-Belts

TPE55D beige smooth



Article no.	Dimensions	Cross section	approx. weight	Standard roll		Recommended min. pulley Ø		Fmax/belt (s-standard)	
	mm	cm ²	kg/100m	m	ft	mm	inch	kg	lbs
FBKH55D08B	8x5 (M)	0,32	4,0	100	328	80	3,2	25,6	56,3
FBKH55D10B	10x6 (Z)	0,48	6,0	50	164	105	4,2	38,4	84,5
FBKH55D13B	13x8 (A)	0,82	10,0	50	164	130	5,1	64,0	140,8
FBKH55D22B	22x14 (C)	2,40	29,0	50	164	250	9,8	192,0	422,4

approx. 55D / 100A

Recommended Pretension 2...4%

Coeff. of friction μ steel approx. 0,35

Coeff. of friction μ PE approx. 0,2

Coeff. of friction μ HDPE approx. 0,15

FDA/EC compliant

Characteristics



FDA (Food and Drug Administration)

FDA/EC conformity for direct food contact



Cold-flexible

Particularly flexible at low temperatures down to -30°C

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 09/2025