
V-Belts

TPE55D beige smooth, Reinforced Polyester



Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley Øø		DRIVE Fmax/belt		TRANSPORT max. conveying weight			
							Standard	Overlap	Standard		Overlap	
	mm	kg/100m	m	ft	mm	inch	N	N	kg	lbs	kg	lbs
FBKH55D10P	10x6 (Z)	6	50	164	110	4,4	229	351	45,8	101,0	70,1	154,6
FBKH55D13P	13x8 (A)	10	50	164	135	5,3	393	474	78,7	173,4	94,8	208,9
FBKH55D17P	17x11 (B)	18	50	164	190	7,2	700	1061	140,0	308,6	212,2	467,7
FBKH55D22P	22x14 (C)	29	50	164	260	10,2	1167	1660	233,5	514,6	332,0	731,8

approx. 55D / 100A	
Max. Preload	
Standard	2 %
Overlap	3 %
Coeff. of friction µ steel approx.	0,35
Coeff. of friction µ PE approx.	0,2
Coeff. of friction µ HDPE approx.	0,15
FDA/EC compliant	

Characteristics

FDA EC

FDA (Food and Drug Administration)
FDA/EC conformity for direct food contact

with reinforcement
for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 10/2026