


V-Belts

PU75A red smooth



approx. 80° Shore A (±3)

Recommended Pretension 4...8%

Coeff. of friction μ steel approx. 0,7

Coeff. of friction μ PE approx. 0,4

Coeff. of friction μ HDPE approx. 0,35

Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley \varnothing		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			mm	kg/100m	m	ft	mm	inch	Standard N
FBKP75A06VZ	6x4 (Y)	1,9	100	328	26	1	17	3,5	7,7
FBKP75A08A	8x5 (M)	3,3	100	328	30	1,2	28	5,7	12,5
FBKP75A10VZ	10x6 (Z)	4,9	50	164	38	1,5	42	8,3	18,3
FBKP75A13B	13x8 (A)	8,6	50	164	56	2,2	76	15,3	33,6
FBKP75A17VZ	17x11 (B)	15,4	50	164	75	3	138	27,6	60,9
FBKP75A22VZ	22x14 (C)	25,2	50	164	108	4,2	230	46,0	101,5

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 07/2026