





Quality: **PU75A**
Article No.: **FBKP75A08A**
Color: **red**

GENERAL PROFILE INFORMATION			
Profile Category	V-belts	k1% relaxed (standard)	3,5 N | 0,8 lbf
Profile design	Without reinforcement	k1% static (standard)	4,4 N | 1,0 lbf
Reinforced	n/a	Weight	3,3 kg/100m
Processing Type	notched	Temperature Range	-20°...+60°C
Recommended Min. pulley Ø	30 mm	Standard Roll	100 m
Recommended Pretension	4...8%	Chemical Resistance	upon request

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	80° Shore A (±3)	n/a
Color	red	n/a
Dimensions	8x5 mm (M)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,7 | PE: 0,4 | HDPE: 0,35	n/a
Features	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 11/2026