
V-Belts

PU75A sky blue smooth



approx. 80° Shore A (±3)	
Recommended Pretension	4...8%
Coeff. of friction µ steel approx.	0,7
Coeff. of friction µ PE approx.	0,4
Coeff. of friction µ HDPE approx.	0,35
FDA/EC compliant	

Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley Øø		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
							Standard	Standard	
	mm	kg/100m	m	ft	mm	inch	N	kg	lbs
FBKI6YLGC	6x4 (Y)	1,9	100	328	26	1	15	3,1	6,8
FBKI8MLGC	8x5 (M)	3,3	100	328	30	1,2	25	5,0	11,0
FBKI10ZLGC	10x6 (Z)	4,8	50	164	38	1,5	37	7,3	16,2
FBKI13ALGF	13x8 (A)	8,4	50	164	56	2,2	67	13,5	29,7
FBKI17BLGAE	17x11 (B)	15,3	50	164	75	3	122	24,4	53,7

Characteristics

FDA/EC
FDA/EC conformity for direct food contact

Vegan
Use of raw materials from non-animal origin

Hydrolysis resistance
Hydrolysis resistance (HY). Suitable for humid environments.

microbial resistant
Microbial resistant materials do not provide a breeding ground for microorganisms.

Cold-flexible
Particularly flexible at low temperatures down to -30°C

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 11/2026