
V-Belts

PU80A ultramarine blue smooth



Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley ∅ø		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
							Standard	Standard	
	mm	kg/100m	m	ft	mm	inch	N	kg	lbs
FBKJ10ZLGD	10x6 (Z)	4,8	50	164	41	1,6	47	9,3	20,5

approx. 84° Shore A (±3)	
Recommended Pretension	4...8%
Coeff. of friction µ steel approx.	0,65
Coeff. of friction µ PE approx.	0,35
Coeff. of friction µ HDPE approx.	0,3
FDA/EC compliant	

Characteristics

FDA/EC
FDA/EC conformity for direct food contact

Vegan
Use of raw materials from non-animal origin

Hydrolysis resistance
Hydrolysis resistance (HY). Suitable for humid environments.

microbial resistant
Microbial resistant materials do not provide a breeding ground for microorganisms.

Cold-flexible
Particularly flexible at low temperatures down to -30°C

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 11/2026