V-Belts

PU85A green smooth



approx. 88° Shore A (±3)	
Recommended Pretension	4...8%
Coeff. of friction µ steel approx.	0,6
Coeff. of friction µ PE approx.	0,35
Coeff. of friction µ HDPE approx.	0,3

Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley Øø		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
							Standard	Standard	
	mm	kg/100m	m	ft	mm	inch	N	kg	lbs
FBKP85A08VZ	8x5 (M)	3,3	100	328	38	1,5	42	8,3	18,3
FBKP85A10VZ	10x6 (Z)	4,9	50	164	49	2	61	12,2	27
FBKP85A13VZ	13x8 (A)	8,6	50	164	71	2,9	112	22,4	49,5
FBKP85A17VZ	17x11 (B)	15,4	50	164	90	3,5	203	40,6	89,6
FBKP85A22VZ	22x14 (C)	25,2	50	164	124	4,9	339	67,7	149,3

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 11/2026