


V-Belts

**PU85A plus blue smooth**



Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			mm	kg/100m	m	ft	mm	inch	Standard N
FBKP85A13BPA	13x8 (A)	8,4	50	164	71	2,8	108	21,5	47,5
FBKP85A17BPV	17x11 (B)	15,3	50	164	90	3,5	195	39,0	86,0
FBKP85A22BA	22x14 (C)	25,2	50	164	124	4,9	325	65,0	143,3

approx. 88° Shore A (±3)

Recommended Pretension	3..6%
------------------------	-------

Coeff. of friction $\mu$ steel approx.	0,6
--	-----

Coeff. of friction $\mu$ PE approx.	0,35
-------------------------------------	------

Coeff. of friction $\mu$ HDPE approx.	0,3
---------------------------------------	-----

**Characteristics**



**Low elongation**  
Patented "PLUS" material mix for reduced elongation.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 07/2026