


V-Belts

PU90A white smooth



approx. 92° Shore A (±3)

Recommended Pretension 3...5%

Coeff. of friction μ steel approx. 0,5

Coeff. of friction μ PE approx. 0,3

Coeff. of friction μ HDPE approx. 0,25

Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley \varnothing		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			mm	kg/100m	m	ft	mm	inch	Standard N
FBKP90A08VZ	8x5 (M)	3,3	100	328	45	1,8	48	9,6	21,1
FBKP90A10E	10x6 (Z)	4,8	50	164	60	2,4	70	14,1	31
FBKP90A13VZ	13x8 (A)	8,4	50	164	79	3,1	129	25,8	56,9
FBKP90A17VZ	17x11 (B)	15,3	50	164	105	4,1	234	46,7	103
FBKP90A22VZ	22x14 (C)	25,2	50	164	150	5,9	389	77,9	171,6

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 07/2026