

V-Belts

# TPE40D beige smooth



approx. 40D / 95A

Recommended Pretension 2...4%

Coeff. of friction  $\mu$  steel approx. 0,5

Coeff. of friction  $\mu$  PE approx. 0,25

Coeff. of friction  $\mu$  HDPE approx. 0,2

FDA/EC compliant

Article no.	Dimensions	approx. weight	Standard roll		Recommended min. pulley $\varnothing$		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			m	ft	mm	inch	Standard N	Standard kg	Standard lbs
FBKR10ZBGVZ	10x6 (Z)	4,8	50	164	60	2,4	71	14,2	31,3
FBKR13ABGZ	13x8 (A)	8,4	50	164	79	3,1	151	30,2	66,6
FBKR17BBGZ	17x11 (B)	15,3	50	164	105	4,1	236	47,1	103,9
FBKR22CBGZ	22x14 (C)	25,2	50	164	150	5,9	393	78,6	173,1

**Characteristics**



**FDA (Food and Drug Administration)**

FDA/EC conformity for direct food contact



**Cold-flexible**

Particularly flexible at low temperatures down to -30°C

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 07/2026