

V-Belts

TPE55D beige smooth



Article no.	Dimensions mm	approx. weight kg/100m	Standard roll		Recommended min. pulley Ø		DRIVE Fmax/belt	TRANSPORT max. conveying weight	
			m	ft	mm	inch	Standard N	Standard kg	Standard lbs
FBKH55D13PZ	13x8 (A)	9,1	50	164	101	4	312	62,5	137,7
FBKH55D17PZ	17x11 (B)	16,1	50	164	143	5,6	488	97,5	215
FBKH55D22PZ	22x14 (C)	26,8	50	164	195	7,7	813	162,5	358,2

approx. 55D / 100A

Recommended Pretension 2...4%

Coeff. of friction μ steel approx. 0,35

Coeff. of friction μ PE approx. 0,2

Coeff. of friction μ HDPE approx. 0,15

FDA/EC compliant

Characteristics



FDA (Food and Drug Administration)

FDA/EC conformity for direct food contact



Cold-flexible

Particularly flexible at low temperatures down to -30°C

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 07/2026