V-guides

PU65A ultramarine blue smooth



	ca. 72° Shore A (±3)
Recommended Pretension	4...8%
Coeff. of friction µ steel approx.	0,8
Coeff. of friction µ PE approx.	0,45
Coeff. of friction µ HDPE approx.	0,4

Order No.	Profile dimension	Standard roll		Recommended min. pulleyø		PT/DRIVE Fmax/Belt	CONVEYANCE Max. load capacity	
						Standard	Standard	
	mm	m	ft	mm	inch	N	kg	lbs
FBKG5X3LG	5x3	150	492	20	0,8	10	1,9	4,2
FBKG6YLG	6x4 (Y)	150	492	30	1,2	15	2,9	6,4
FBKG8MLG	8x5 (M)	150	492	35	1,4	25	5,0	11,1
FBKG10ZLG	10x6 (Z)	150	492	40	1,6	38	7,6	16,8
FBKG13ALG	13x8 (A)	150	492	65	2,6	66	13,1	28,9
FBKG17BLG	17x11 (B)	100	328	85	3,4	117	23,3	51,4
FBKG22CLG	22x14 (C)	50	164	120	4	195	38,9	85,8

Characteristics

Hydrolysis resistance
Hydrolysis resistance (HY). Suitable for humid environments.

microbial resistant
Microbial resistant materials do not provide a breeding ground for microorganisms.

FDA/EC
FDA/EC conformity for direct food contact

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 2026-11-25 15:10