

Quality: PU70A
Order No.: FBKH8MLGA
Color: sky blue

FDA
EC

GENERAL PROFILE INFORMATION			
Profile Category	Guides and Profiles	k1% relaxed (standard)	2,3 N | 0,5 lbf
Profile Design	n/a	k1% static (standard)	2,9 N | 0,6 lbf
Processing Type	n/a	Temperature Range	-20°...+60°C
Recommended min. pulley	30 mm	Standard roll	150 m
Recommended pretension	4...8%	Chemical Resistance	upon request

SPECIFICATIONS	PROFILE	COATING
Type of Material	Polyurethane	n/a
Approx. material hardness (Shore)	76° Shore A	n/a
Color	sky blue	n/a
Dimensions	8x5 mm (M)	n/a
Surface	smooth	n/a
Approx. coefficients of friction µ	Steel: 0,75 | PE: 0,4 | HDPE: 0,35	n/a
Features	FDA/EC	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a

CONFORMITY
REACH EC 1907/2006 in the current versions
EC 1935/2004 in the current versions
EC 10/2011 in the current versions
FDA (Food and Drug Administration)

The above information is based on the results of our internal quality control. It does not constitute a guarantee of any properties and, in particular, does not contain any statements regarding the product's suitability for specific purposes; therefore, no claims against us may be derived from this information. In particular, this information does not relieve the buyer of the obligation to inspect the goods upon receipt.

Subject to change without notice - 2026-11-26 08:54