V-guides

PU70A transparent smooth



	ca. 76° Shore A
Recommended Pretension	4...8%
Coeff. of friction µ steel approx.	0,75
Coeff. of friction µ PE approx.	0,4
Coeff. of friction µ HDPE approx.	0,35

Order No.	Profile dimension	Standard roll		Recommended min. pulleyø		PT/DRIVE Fmax/Belt	CONVEYANCE Max. load capacity	
						Standard	Standard	
	mm	m	ft	mm	inch	N	kg	lbs
FBKH5X3TG	5x3	150	492	25	1	10	2,1	4,6
FBKH6YTG	6x4 (Y)	150	492	30	1,2	16	3,2	7,1
FBKH8MTG	8x5 (M)	150	492	35	1,4	28	5,5	12,2
FBKH10ZTG	10x6 (Z)	150	492	45	1,8	42	8,4	18,5
FBKH13ATG	13x8 (A)	150	492	70	2,8	72	14,4	31,8
FBKH17BTG	17x11 (B)	100	328	90	3,6	128	25,7	56,6
FBKH22CTG	22x14 (C)	50	164	130	5,2	214	42,8	94,3

Characteristics

FDA EC

FDA/EC
FDA/EC conformity for direct food contact

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 2026-11-25 01:56