

Quality: **PU75A**
Order No.: **FBFI8X8LG**
Color: **ultramarine blue**

GENERAL PROFILE INFORMATION			
Profile Category	Guides and Profiles	k1% relaxed (standard)	9,6 N | 2,2 lbf
Profile Design	n/a	k1% static (standard)	12,1 N | 2,7 lbf
Processing Type	n/a	Temperature Range	-20°...+60°C
Recommended min. pulley	75 mm	Standard roll	50 m
Recommended pretension	4...8%	Chemical Resistance	upon request

SPECIFICATIONS	PROFILE	COATING
Type of Material	Polyurethane	n/a
Approx. material hardness (Shore)	80° Shore A	n/a
Color	ultramarine blue	n/a
Dimensions	8x8 mm	n/a
Surface	smooth	n/a
Approx. coefficients of friction µ	Steel: 0,7 | PE: 0,4 | HDPE: 0,35	n/a
Features	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a

CONFORMITY

The above information is based on the results of our internal quality control. It does not constitute a guarantee of any properties and, in particular, does not contain any statements regarding the product's suitability for specific purposes; therefore, no claims against us may be derived from this information. In particular, this information does not relieve the buyer of the obligation to inspect the goods upon receipt.

Subject to change without notice - 2026-11-26 08:54