


Material: **TGA**



Material: **FI**



Material: **PU55A / PU80A**

Material: **FBFOJ750X25A**

Technical Data

Material	Material	Material	Material 2
Material	2,5 mm	Material	1,52 kg/m ²
Material	18 mm	Material	-20°C...+60°C
Material	1...5%	Material	750 mm
1% Material	0,4 N/mm	Material	730 mm
1% Material	0,3 N/mm	Material	Material

Material	Material	Material
Material	60° Shore A (±3)	84° Shore A (±3)
Material μ	1,2	0,5
Material	Material	Material
Material	1,5 mm	1 mm
Material	Material TGA	Material FI
Material	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
Material	Material	Material
Material	Material	Material Rg = <10E09Ω (1GΩ)
Material	Material	2K
Material	Material Rg = <10E09Ω (1GΩ)	
Material	MicroClean	
Material	2K	

Material	Material	Material	Material
REACH EC 1907/2006	Material	Material	Material
EG 1935/2004	Material	Material	260°C ±10°C
EG 10/2011	Material	Material	
FDA (Food and Drug Administration)	Material	Material	

Material

Material

Material


Material - 10/2026

Icons

BEHAbelt icons represent the various properties of the belts.




Complies with FDA/EC standards



Electrostatically dissipative




Complies with X-ray standards PU SAFE




Antibacterial



Waterproof



Micro Clean



UV-C resistant



2K




Vegan



ISO 340




Curved



Curved

Applications

BEHAbelt belts are used in various applications.




PU and TPE belts



PU and TPE belts



PU and TPE belts



PU and TPE belts



PU and TPE belts