

□□□: □□□□□SR□



000: 000000FI



PU65A / PU55D

□□:
FBFNG750X19S

Technische Daten			
Material	Aluminium	Material	Aluminium 2024-T3
Stärke	1,9 mm	Gewicht	2,28 kg/m²
Stärke	21 mm	Temperaturbereich	-30°...+60°C
Stärke	0.5...3%	Stärke	750 mm
1% Stabilität	0,82 N/mm	Stärke	730 mm
1% Stabilität	0,58 N/mm	Stärke	700 mm

項目	規格	規格
硬さ (Shore A)	72° Shore A (±3)	55° Shore D (±3)
硬さ (Shore D)	0,7	0,25
厚さ	0,8 mm	1,1 mm
材質	シリコンSR	シリコンFI
承認	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
電圧	0V	0V
電圧	0V Rg = <10E09Ω (1GΩ)	0V Rg = <10E09Ω (1GΩ)
電圧	2K	2K

REACH	EC 1907/2006	RoHS
EG	1935/2004	RoHS
EG	10/2011	RoHS
IEC	61340-2-3/EN61340-5-1	RoHS
FDA	(Food and Drug Administration)	

Copyright © 2017 Pearson Education, Inc. All rights reserved.

□□□□□□□□□□□□□□ - 09/2026

1111

BEHAbelt 

□□□□□□□□□□FDA/EC□□□





XXXXXXXXXXXXXXXXXXXXXXXPU
SAFEXXXXXXXXXX



□ □

[illegible]


□□□□□□□□□□□□□□

[illegible][illegible][illegible][illegible]

2|




ISO 340□□□□□□□□



□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

□ □ □ □ □ □ □ □

[illegible]

PU TPE




PU TPE



PU TPE



□□□□□□□□V□□□□□□PU□□□□□□
□



PU□□□□□□