

□□□: □□□□□**SR**□



000: 000000FI



□□:
PU80A

□□:
FBFJ750X12LA

Technische Daten			
Plattendicke	Plattenbreite	Plattenlänge	Plattengewicht
1,2 mm	1.2 mm	1,44 m	1,44 kg/m²
10 mm	10 mm	-20°C...+60°C	
1...5%	1...5%	750 mm	
0,33 N/mm	0,33 N/mm	730 mm	
0,23 N/mm	0,23 N/mm	730 mm	

項目	仕様	実測値
動作温度範囲	84° Shore A (±3)	84° Shore A (±3)
動作湿度 μ	0.5	0.5
圧	標準動作範囲	標準動作範囲
動作電圧	n/a	n/a
電圧	標準動作SR	標準動作FI
動作電圧	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
	動作電圧	動作電圧
	動作電圧Rg = <10E09Ω (1GΩ)	動作電圧Rg = <10E09Ω (1GΩ)

REACH	EC 1907/2006	EU
EG	1935/2004	EU
EG	10/2011	EU
IEC61340-2-3/EN61340-5-1		IEC
FDA (Food and Drug Administration)		USA

[illegible][illegible]

00000000000000 - 09/2026

BEHAbelt

BEHAbelt 提供多種規格之工業用橡膠帶，適用於各種工業應用。




符合FDA/EC標準



符合X光機安全標準，不含鉛，PU SAFE



具有優異之防水性能




UV-C 耐光性



純素材料



可彎曲橡膠帶



具有優異之導電性能



具有優異之抗菌性能




具有優異之清潔性能



2K 雙組份橡膠帶




ISO 340 標準



可彎曲橡膠帶

產品系列

提供多種規格之工業用橡膠帶




PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 橡膠帶