



Material: **SG**



Material: **SG**



Material: **PU80A**

Material: **FBFJ150X240G**

Technical Data

Material	Material	Material	Material
Material	2,4 mm	Material	2,88 kg/m ²
Material	25 mm	Material	-20°C...+60°C
Material	1...5%	Material	150 mm
1%Material	0,72 N/mm	Material	140 mm
1%Material	0,5 N/mm	Material	Material

Material	Material	Material
Material	84° Shore A (±3)	84° Shore A (±3)
Material μ	0,65	0,65
Material	Material	Material
Material	n/a	n/a
Material	Material (SG)	Material (SG)
Material	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
	Material	Material

Material
REACH/EC 1907/2006Material
EG 1935/2004Material
EG 10/2011Material
FDA (Food and Drug Administration)

Material			
Material		Material	
Material	160 °C	Material	260°C ±10°C
Material	0,5 bar		
Material	90 sek.		

Material is a registered trademark of BEHA Innovation GmbH. All rights reserved. Material is a registered trademark of BEHA Innovation GmbH. All rights reserved.


Material - 10/2026

Icons

BEHAbelt icons represent various properties and certifications of the belts.




Belts are FDA/EC approved



Belts are static dissipative




Belts are X-ray safe (PU SAFE)




Belts are microorganism resistant



Belts are water resistant



Belts are micro clean



UV-C resistant



2-component belts




Belts are vegan



ISO 340 certified




Belts are flexible



Belts are flexible

Applications

Belts are used in various applications.



PU and TPE belts



PU and TPE belts



PU and TPE belts



V-belt PU



PU belts