

□□□: □□□□□□ (SG)



□□□: □□□□□□ (SG)



□□:
PU85A

FBFK150X2GG

Technische Daten			
Material	Alu-Mg-Si	Material	Alu-Mg-Si
Stärke	2 mm	Dichte	2,4 kg/m²
Stärke	30 mm	Temperaturbereich	-20°C...+60°C
Stärke	1...5%	Stärke	150 mm
1%Stärke	0,63 N/mm	Stärke	140 mm
1%Stärke	0,5 N/mm	Stärke	Stärke

項目	単位	単位
表面硬度 (Shore A)	88° Shore A (±3)	88° Shore A (±3)
表面粗さ (Ra)	0,6	0,6
色	白色	白色
透過率	n/a	n/a
重量	約 10g (SG)	約 10g (SG)
寸法		

FDA (Food and Drug Administration)

[illegible][illegible]

00000000000000000000 - 10/2026

BEHAbelt

BEHAbelt 提供多種規格之工業用橡膠帶，適用於各種工業應用。




符合 FDA/EC 標準



符合 X 光機安全標準 (METAL X-RAY SAFE)



具有優異之防水性能




UV-C 光線耐性



符合 VEGAN 標準



具有優異之彎曲性能



具有優異之導電性能



具有優異之抗菌性能




符合 MICRO CLEAN 標準



2 組式橡膠帶




符合 ISO 340 標準



具有優異之彎曲性能

產品系列

提供多種規格之工業用橡膠帶



PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 橡膠帶