

□□□: □□□□□**SR**□



000: 000000FI



□□:
PU80A

□□:
FBFJ750X09LA

Technische Daten			
Material	Alu-Mg-Si	Material	Alu-Mg-Si
Stärke	0,9 mm	Dichte	1,05 kg/m²
Stärke	8 mm	Temperaturbereich	-20°C...+60°C
Stärke	1...5%	Stärke	750 mm
1%Stärke	0,24 N/mm	Stärke	730 mm
1%Stärke	0,17 N/mm	Stärke	Stärke

項目	仕様	実測値
動作温度範囲	84° Shore A (±3)	84° Shore A (±3)
動作湿度 μ	0.5	0.5
圧	標準動作範囲	標準動作範囲
動作電圧	n/a	n/a
電	標準動作SR	標準動作FI
動作電圧	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
	電圧	電圧
	動作電圧範囲 Rg = <10E09Ω (1GΩ)	動作電圧範囲 Rg = <10E09Ω (1GΩ)

REACH	EC 1907/2006	EU
EG	1935/2004	EU
EG	10/2011	EU
IEC61340-2-3/EN61340-5-1		IEC
FDA (Food and Drug Administration)		USA

[illegible][illegible]


00000000000000 - 10/2026

Icons

BEHAbelt icons represent various properties and certifications of the belts.




Belts are FDA/EC approved



Belts are static dissipative



Belts are X-ray safe (PU SAFE)




Belts are microorganism resistant



Belts are water resistant



Belts are micro clean



UV-C resistant



2-component belts




Belts are vegan



ISO 340 certified




Belts are flexible



Belts are flexible

Applications

Belts are used in various applications:



PU and TPE belts



PU and TPE belts



PU and TPE belts



V-belt and PU belt



PU belt