

Material: **SM**



Material: **FI**



Material: **PU75A**

Material: **FBFI750X10WA**

Mechanical Properties			
Thickness	1 mm	Density	1,2 kg/m³
Thickness	10 mm	Temperature Range	-30°C...+50°C
Compression Set	1...5%	Width	750 mm
1% Modulus	0,21 N/mm	Width	730 mm
1% Modulus	0,15 N/mm	Width	750 mm

Physical Properties		
Shore A Hardness	80° Shore A (±3)	80° Shore A (±3)
Permeability (μ)	0,65	0,55
Porosity	n/a	n/a
Material	SM	FI
Approval	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
MicroClean	MicroClean	MicroClean

Regulatory Compliance
REACH EC 1907/2006
EG 1935/2004
FDA (Food and Drug Administration)

Thermal Properties			
Temperature	155 °C	Temperature	260°C ±10°C
Pressure	0.5 bar		
Time	30 sek.		

BEHA Innovation GmbH is a company of the BEHA Group. The company is located in the Engematten 16, 79286 Glottertal, Germany. The company is a member of the BEHA Group, which is a leading manufacturer of industrial belts and hoses. The company is also a member of the BEHA Group, which is a leading manufacturer of industrial belts and hoses.

Version: 10/2026

BEHAbelt

BEHAbelt 提供多種規格之工業用橡膠帶，適用於各種工業應用。




符合FDA/EC標準



符合X光機安全標準，適用於醫療設備PU SAFE



具有優異之防水性能




UV-C 抗紫外線



符合素食標準



具有優異之彎曲性能



具有優異之導電性能



具有優異之抗菌性能




具有優異之清潔性能



2K 雙組份系統




ISO 340 標準



具有優異之彎曲性能

產品系列

提供多種規格之工業用橡膠帶



PU 及 TPE 工業用橡膠帶



PU 及 TPE 工業用橡膠帶



PU 及 TPE 工業用橡膠帶



三角帶及 PU 工業用橡膠帶



PU 工業用橡膠帶