

□□□: □□□□□□□□SM□



000: 000000FI



□□:
PU75A

FBFI750X20WA

Technische Daten			
Plattendicke	Plattenbreite	Plattenlänge	Plattengewicht
2 mm	20 mm	2,4 kg/m²	-20°C...+60°C
1...5%	750 mm	730 mm	
0,43 N/mm	0,3 N/mm		

項目	規格	規格
硬度 (Shore A)	80° Shore A (±3)	80° Shore A (±3)
弾性率 (μ)	0,65	0,55
密度	1,05	1,05
耐熱性	n/a	n/a
耐薬品性	耐薬品性SM	耐薬品性FI
規格	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
	規格	規格
	規格	規格
	規格	規格
	MicroClean	

REACH (EC 1907/2006)

EG 1935/2004

FDA (Food and Drug Administration)

[illegible][illegible]


□□□□□□□□□□□□□□ - 10/2026

Icons

BEHAbelt icons represent various properties and certifications of the belts.




Belts are FDA/EC approved



Belts are static dissipative




Belts are X-ray safe (PU SAFE)




Belts are microorganism resistant



Belts are water resistant



Belts are micro clean



UV-C resistant



2-component system




Belts are vegan



ISO 340 certified




Belts are flexible



Belts are flexible

Applications

Belts are used in various applications.



PU and TPE belts



PU and TPE belts



PU and TPE belts



V-belt PU



PU belts