

□□□: □□□□□□□□SM□



000: 00000FI0



□□:

PU95A

□□:

FBFL750X16WA

Technische Daten			
Material	Alu-Mg-Si	Material	Alu-Mg-Si
Stärke	1,6 mm	Dichte	1,92 kg/m³
Stärke	25 mm	Temperaturbereich	-30°...+60°C
Stärke	0.5...3%	Stärke	750 mm
1%Stärke	0,82 N/mm	Stärke	730 mm
1%Stärke	0,58 N/mm	Stärke	Stärke

項目	規格	検査方法
硬度	95° Shore A (±3)	95° Shore A (±3)
伸び率 μ	0,4	0,3
密度	規格	規格
耐熱性	n/a	n/a
耐薬品性	規格参照SM	規格参照FI
承認	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
消毒	規格	規格
	規格	規格
	規格参照	規格参照
	規格参照	規格参照
	MicroClean	

REACH/EC 1907/2006
EG 1935/2004
FDA (Food and Drug Administration)

[illegible][illegible]

□□□□□□□□□□□□□□ - 10/2026

BEHAbelt

BEHAbelt 提供多種規格之工業用橡膠帶，適用於各種工業應用。




符合FDA/EC標準



符合X光機安全標準PU SAFE



具有優異之防水性能




UV-C 耐光性



純素製品



多種規格之工業用橡膠帶



具有優異之導電性能



具有優異之抗菌性能




具有優異之清潔性能



2K 雙組份橡膠帶




ISO 340 標準



多種規格之工業用橡膠帶

產品系列

提供多種規格之工業用橡膠帶




PU 及 TPE 工業用橡膠帶



PU 及 TPE 工業用橡膠帶



PU 及 TPE 工業用橡膠帶



多種規格之 V 型工業用橡膠帶



PU 工業用橡膠帶