

□□□: □□□□□□□□SM□



000: 00000FI



□□:
PU95A

FBFL750X20WA

Technische Daten			
Plattendicke	2 mm	Plattenbreite	2,4 kg/m²
Plattenhöhe	35 mm	Plattentemperatur	-30°...+60°C
Plattenabstand	0.5...3%	Plattenlänge	750 mm
1%Plattenabstand	1,03 N/mm	Plattenbreite	730 mm
1%Plattenabstand	0,72 N/mm	Plattenhöhe	35 mm

項目	規格	検査方法
硬度 (Shore A)	95° Shore A (±3)	95° Shore A (±3)
伸び率 (%)	0,4	0,3
引張強度 (MPa)	0,05	0,05
引張変形率 (%)	n/a	n/a
耐熱性 (°C)	150°C (短期)	150°C (短期)
耐薬品性	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
滅菌性	滅菌可能	滅菌可能
加工性	加工可能	加工可能
透気性	透気可能	透気可能
電気特性	電気絶縁性	電気絶縁性
環境適合性	MicroClean	MicroClean

REACH (EC 1907/2006)

EG 1935/2004

FDA (Food and Drug Administration)

[illegible][illegible]

□□□□□□□□□□□□□□ - 10/2026

BEHAbelt

BEHAbelt 提供多種規格之工業用橡膠帶，適用於各種工業應用。




符合FDA/EC標準



符合X光機安全標準，PU SAFE



具有優異之防水性能




UV-C 耐光性



純素製品



可彎曲橡膠帶



具有優異之導電性能



具有優異之抗菌性能




具有優異之清潔性能



2K 雙組份橡膠帶




ISO 340 標準



可彎曲橡膠帶

產品系列

提供多種規格之工業用橡膠帶




PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



具有優異之導電性能之 PU 橡膠帶



PU 橡膠帶