

Material: **SM**



Material: **FI**



Material: **PU95A**

Material: **FBFL750X30WA**



Technical Data			
Material	SM	Material	FI
Thickness	3 mm	Weight	3,6 kg/m²
Width	50 mm	Temperature Range	-30°...+60°C
Porosity	0.5...3%	Length	750 mm
1% Elongation	1,54 N/mm	Width	730 mm
1% Elongation	1,08 N/mm	Material	FBFL750X30WA

Property	SM	FI
Shore A Hardness	95° Shore A (±3)	95° Shore A (±3)
Permeability μ	0,4	0,3
Color	White	White
Flammability	n/a	n/a
Material	SM	FI
Certification	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
MicroClean	MicroClean	MicroClean

Regulation
REACH EC 1907/2006
EG 1935/2004
FDA (Food and Drug Administration)

Thermal Properties			
Material	SM	Material	FI
Temperature	175 °C	Temperature	260°C ±10°C
Time	120 sek.	Time	

BEHA Innovation GmbH is a company of the BEHA Group. The BEHA Group is a leading manufacturer of high-quality technical rubber products. The BEHA Group is a member of the BEHA Group of Companies. The BEHA Group of Companies is a leading manufacturer of high-quality technical rubber products. The BEHA Group of Companies is a member of the BEHA Group of Companies.

Version: 10/2026

BEHAbelt

BEHAbelt 提供多種規格之工業用橡膠帶，適用於各種工業應用。




符合FDA/EC標準



符合X光機安全標準，適用於醫療設備PU SAFE



具有優異之防水性能




UV-C光線保護



純素製品



具有優異之彎曲性能



具有優異之導電性能



具有優異之抗菌性能




符合MICRO CLEAN標準



2K雙組份系統




ISO 340標準



具有優異之彎曲性能

產品系列

提供多種規格之工業用橡膠帶



PU及TPE工業橡膠帶



PU及TPE工業橡膠帶



PU及TPE工業橡膠帶



具有優異之彎曲性能之PU工業橡膠帶



PU工業橡膠帶