



Material: **SG**



Material: **SR**



Material: **PU80A**

Material: **FBFJ750X16T**

Technical Data

Material	Material	Material	Material
Material	1,6 mm	Material	1,92 kg/m ²
Material	15 mm	Material	-20°C...+60°C
Material	1...5%	Material	750 mm
1%Material	0,48 N/mm	Material	730 mm
1%Material	0,34 N/mm	Material	Material

Material	Material	Material
Material	84° Shore A (±3)	84° Shore A (±3)
Material μ	0,65	0,5
Material	Material	Material
Material	n/a	n/a
Material	Material (SG)	Material SR
Material	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
	Material	Material

Material	Material	Material
REACH EC 1907/2006	Material	Material
EG 1935/2004	Material	Material
FDA (Food and Drug Administration)	Material	Material

Material: Material (SG) Material SR


Material - 10/2026

Icons

BEHAbelt icons represent the various properties and features of our products.




Complies with FDA/EC standards



Electrostatic discharge (ESD) protection




Complies with X-ray standards (PU SAFE)




Antibacterial properties



Waterproof and oil-resistant



Micro Clean technology



UV-C resistant



2K system




Vegan



ISO 340




Curved line



Curved line

Applications

Applications of BEHAbelt products:




PU and TPE material roll



PU and TPE material pieces



PU and TPE material being processed



PU and TPE material being processed



PU and TPE material being processed