

□□□: □□□□□□ (ID)



000: 00000FI0



□□:
PU95A

FBFM750X25LH

Technische Daten			
Material	Aluminium	Material	Aluminium
Dicke	2,5 mm	Dichte	kg/m ³
Stärke	40 mm	Temperaturbereich	-20°C...+60°C
Stärkeabweichung	0.5...3%	Stärke	750 mm
1%Stärkeabweichung	1,22 N/mm	Stärke	730 mm
1%Stärkeabweichung	0,86 N/mm	Stärke	Stärke

項目	規格	試験方法
硬度	95° Shore A (±3)	95° Shore A (±3)
弾性率 μ	0,25	0,3
密度	1.05 g/cm³	1.05 g/cm³
引張強度	n/a	n/a
伸び	100% (ID)	100%FI
規格	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
	MicroClean	

REACH (EC 1907/2006)

EG 1935/2004

FDA (Food and Drug Administration)

Свойства материала			
Материал		Полипропилен	
Температура эксплуатации	175 °C	Температура хранения	260°C ±10°C
Время жизни			
Время монтажа	120 sek.		

[illegible]


□□□□□□□□□□□□□□ - 10/2026

Icons

BEHAbelt icons represent various properties and certifications of the belts.




Belts are FDA/EC approved



Belts are static dissipative




Belts are X-ray safe (PU SAFE)




Belts are microorganism resistant



Belts are water resistant



Belts are micro clean



UV-C resistant



2-component system




Belts are vegan



ISO 340 certified




Belts are flexible



Belts are flexible

Applications

Belts are used in various applications.



PU and TPE belts



PU and TPE belts



PU and TPE belts



V-belt PU



PU belts