

格式: TGA



000: 00000FI0



□□:
PU95A

FBFM750X25LB

Technische Daten			
Material	Alu-Mg-Si	Profil	Alu-Mg-Si
Stärke	2,5 mm	Dichte	2,4 kg/m³
Stärke	40 mm	Temperaturbereich	-20°C...+60°C
Stärke	0.5...3%	Stärke	750 mm
1%Stärke	0,87 N/mm	Stärke	730 mm
1%Stärke	0,61 N/mm	Stärke	Stärke

項目	規格	検査方法
硬度（ Shore A ）	95° Shore A (±3)	95° Shore A (±3)
伸び率 (%)	n/a	0,3
密度 (g/cm³)	約 1.2	約 1.2
耐熱性 (°C)	n/a	n/a
耐水性	ISO 7266-2	ISO 7266-2
耐油性	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
耐薬品性	ISO 7266-2	ISO 7266-2
耐摩擦性	MicroClean	MicroClean

REACH (EC 1907/2006)

EG 1935/2004

FDA (Food and Drug Administration)

Свойства и характеристики			
Материал корпуса		Алюминий	
Температура хранения	175 °C	Температура эксплуатации	260°C ±10°C
Время работы			
Время зарядки	120 сек.		

Copyright © 2017 Pearson Education, Inc. All rights reserved.

00000000000000000000 - 10/2026

BEHAbelt

BEHAbelt 提供多種規格之工業用橡膠帶，適用於各種工業應用。




符合FDA/EC標準



符合X光機安全標準，適用於醫療設備PU SAFE



具有優異之防水性能




UV-C 抗紫外線



純素製品



可彎曲橡膠帶



具有優異之導電性能



具有優異之抗菌性能




具有優異之清潔性能



2K 雙組份橡膠帶




ISO 340 標準



可彎曲橡膠帶

產品系列

提供多種規格之工業用橡膠帶




PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



V 型橡膠帶及 PU 橡膠帶



PU 橡膠帶