

RI



(ID)



PU75A

FBF1750X30LC

BEHAbelt

Material	3 mm	Weight	3,6 kg/m²
Thickness	30 mm	Temperature range	-30°C...+50°C
Porosity	1...5%	Width	750 mm
1% Porosity	0,51 N/mm	Length	730 mm
1% Porosity	0,36 N/mm	Material	PU75A

Property	RI	(ID)
Shore A hardness	80° Shore A (±3)	80° Shore A (±3)
Permeability μ	0,5	0,5
Material	PU75A	PU75A
Width	n/a	n/a
Length	750 mm	730 mm
Material	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
Material	MicroClean	MicroClean

REACH EC 1907/2006
EG 1935/2004
FDA (Food and Drug Administration)

Temperature	155 °C	Temperature	260°C ±10°C
Pressure	0,5 bar		
Time	120 sek.		

BEHAbelt is a registered trademark of BEHA Innovation GmbH. All rights reserved.

BEHAbelt - 10/2026

BEHAbelt

BEHAbelt 提供多種規格之工業用橡膠帶，適用於各種工業應用。




符合FDA/EC標準



符合X光機安全標準，不含鉛，PU SAFE



具有優異之防水性能




UV-C 耐光性



純素製品



可彎曲橡膠帶



具有優異之導電性能



具有優異之抗菌性能




具有優異之清潔性能



2K 雙組份橡膠帶




ISO 340 標準



可彎曲橡膠帶

產品系列

提供多種規格之工業用橡膠帶



PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 及 TPE 橡膠帶



PU 橡膠帶